
























CHIUSURE PNEUMATICHE - PNEUMATIC CLAMPS

<p>Chiusura Pneumatica Pneumatic Clamp</p> <p>CPR25</p>  <p>Diam. 25mm Clamp. 30Nm Hold. 75Nm Ang. 15-105° Weight. 2,0Kg.</p> <p>PDF Catalogue</p>	<p>Chiusura Pneumatica Pneumatic Clamp</p> <p>CPL40</p>  <p>Diam. 40mm Clamp. 140Nm Hold. 380Nm Ang. 2-135° Weight. 2,2-2,7Kg.</p> <p>PDF Catalogue</p>	<p>Chiusura Pneumatica Pneumatic Clamp</p> <p>CPL50/63</p>  <p>EU Norm Diam. 50/63mm Clamp. 250/420Nm Hold. 1.300/1.700Nm Ang. 2,5-135° Weight. 4,0/5,0Kg.</p> <p>PDF Catalogue</p>	<p>Chiusura Pneumatica Pneumatic Clamp</p> <p>CPL80</p>  <p>EU Norm Diam. 80mm Clamp. 1.000Nm Hold. 2.500Nm Ang. 3-135° Weight. 14Kg.</p> <p>PDF Catalogue</p>
<p>Chiusura Pneumatica Pneumatic Clamp</p> <p>CPLV50/63</p>  <p>Toll.Comp.(V). 10mm/230mm EU Norm Diam. 50/63mm Clamp. 200/280Nm Hold. 200/280Nm Ang. 2,5-135° Weight. 4,0/5,0Kg.</p> <p>PDF Catalogue</p>	<p>Chiusura Manuale Manual Clamp</p> <p>MC</p>  <p>HeavyDuty SteelBody Manual Hold. 160Nm Ang. 60-120° Weight. 4,3Kg.</p> <p>PDF Catalogue</p>	<p>Chiusura Pneumatica Pneumatic Clamp</p> <p>CPN50/63</p>  <p>NAAMS Standard Diam. 50/63mm Clamp. 250/420Nm Hold. 1.300/1.700Nm Ang. 2,5-135° Weight. 4,0/5,0Kg.</p> <p>NAAMS</p> <p>PDF Catalogue</p>	<p>Chiusura Pneumatica Pneumatic Clamp</p> <p>CPN80</p>  <p>NAAMS Standard Diam. 80mm Clamp. 1.000Nm Hold. 2.500Nm Ang. 3-135° Weight. 11,5Kg.</p> <p>NAAMS</p> <p>PDF Catalogue</p>
<p>Chiusura Pneumatica Pneumatic Clamp</p> <p>CPR50/63</p>  <p>HeavyDuty SteelBody Diam. 50/63mm Clamp. 270/420Nm Hold. 1.000 Ang. 15-120° Weight. 5,0/5,5Kg.</p> <p>PDF Catalogue</p>	<p>Chiusura Pneumatica Pneumatic Clamp</p> <p>DL63</p>  <p>HeavyDuty SteelBody Diam. 63mm Clamp. 400Nm Hold. 600Nm Ang. 45-90° Weight. 10,0Kg.</p> <p>PDF Catalogue</p>		

GRIPPER PNEUMATICI - PNEUMATIC GRIPPERS

<p>Gripper pneumatico Pneumatic Gripper</p> <p>B32A/B</p>  <p>Diam. 32mm Clamp. 850N/250N Ang. 22,5-160° Weight. 1,3-1,5Kg.</p> <p>PDF Catalogue</p>	<p>Gripper pneumatico Pneumatic Gripper</p> <p>B40A/B B40VA/B</p>  <p>Diam. 40mm TolleranceComp. (V) Clamp. 1.400/600N Clamp(V). 1.050/460N Ang. 22,5-160° Weight. 2,5Kg.</p> <p>PDF Catalogue</p>	<p>Gripper pneumatico Pneumatic Gripper</p> <p>G40.1</p>  <p>Diam. 40mm Clamp. 130Nm Hold. 200Nm Ang. 15-105° Weight. 1,8Kg.</p> <p>PDF Catalogue</p>	<p>Gripper per Transfer Transfer Gripper</p> <p>G20</p>  <p>Diam. 22mm Clamp. 20Nm Hold. 50Nm Ang. 15-90° Weight. 0,8Kg.</p> <p>PDF Catalogue</p>
---	--	--	--










DISPOSITIVI DI CENTRAGGIO - LOCATOR DEVICE

<p>Disp. Centraggio Locator Device</p> <p>DCP30.1</p>  <p>Diam. 30mm Stroke. 20-40mm PushForce. 350N PullForce. 250N RadialForce. 70N AxialTorque. 4Nm Weight. 0,8-1,1Kg.</p> <p>PDF Catalogue</p>	<p>Disp. Centraggio Locator Device</p> <p>DCP40</p>  <p>Diam. 40mm Stroke. 20-60mm PushForce. 600N PullForce. 500N RadialForce. 150N AxialTorque. 4-6Nm Weight. 1,7-2,0Kg.</p> <p>PDF Catalogue</p>	<p>Disp. Centraggio Locator Device</p> <p>DCP63.1</p>  <p>Diam. 63mm Stroke. 20-60mm PushForce. 1500N PullForce. 1400N RadialForce. 200N AxialTorque. 4-6Nm Weight. 2,8-3,1Kg.</p> <p>PDF Catalogue</p>	<p>Disp. Centraggio Locator Device</p> <p>DCP40 (CNOMO STANDARD)</p>  <p>Diam. 40mm Stroke. 25-50mm PushForce. 600N PullForce. 500N RadialForce. 150N AxialTorque. 4-6Nm Weight. 1,7-2,0Kg.</p> <p>CNOMO</p> <p>PDF Catalogue</p>
<p>Disp. Centraggio Locator Device</p> <p>DCPD40W</p>  <p>Diam. 40mm Stroke. 20-40mm PushForce. 600N PullForce. 500N RadialForce. 80N Ma. 6Nm Mb. 3Nm Weight. 1,1-1,2Kg.</p> <p>PDF Catalogue</p>	<p>Disp. Centraggio Locator Device</p> <p>DCPD63.1</p>  <p>Diam. 63mm Stroke. 20-60mm PushForce. 1500N PullForce. 1350N RadialForce. 200N Ma. 60Nm Mb. 30Nm Weight. 3,6-3,8Kg.</p> <p>PDF Catalogue</p>	<p>Disp. Centraggio Locator Device</p> <p>DCPD50U</p>  <p>Toggle Lock System Diam. 50mm Stroke. 40mm PushForce. 1000N PullForce. 800N RadialForce. 400N Ma/Mb 40/80Nm Weight. 6,7-7,0Kg.</p> <p>PDF Catalogue</p>	

Cancelare la cache del web browser per essere sicuri di scaricare l'ultima versione dei cataloghi o dei 3Ds / Cancel your web browser cache in order to be sure to download the last release catalogues or 3Ds







SUBLEVELS - UNDERBODYCLAMPS

<p>Sublevel UnderbodyClamp DCA50.2</p>  <p>SteelBody Diam. 50mm Clamp. 400dN Hold. 470dN HighStrengthPin PinØ. 20-40mm Weight. 5,7Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DCA50R.1</p>  <p>SteelBody Diam. 50mm Clamp. 250dN Hold. 380dN HighStrengthPin PinØ. 18-40mm Weight. 3,4Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel Orizzontale Horiz. UnderbodyClamp DCA50Z.1</p>  <p>Horizontal LayOut AluBody Diam. 50mm Clamp. 200dN Hold. 330dN HighStrengthPin PinØ. 18-30mm Weight. 3,0Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DCA40G</p>  <p>LightWeight AluBody Diam. 40mm Clamp. 110dN Hold. 200dN HighStrengthPin PinØ. 16-32mm Weight. 1,8Kg.</p> <p>PDF Catalogue</p>
<p>Sublevel UnderbodyClamp DCA63V.2/V6</p>  <p>NEW Toll.Comp (V) 3mm opz.(V6) 6mm Diam. 63mm Clamp. 220-280dN Hold. 330dN HighStrengthPin PinØ. 20-40mm Weight. 7,0Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DCA63LxV</p>  <p>90° Rotable Hook Toll.Comp.(V). 3mm Diam. 63mm Clamp. 200-280dN Hold. 330dN HighStrengthPin PinØ. 20-40mm Weight. 7,0Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DCA63CV</p>  <p>SteelBody Pin-Hole Gap Comp. Toll.Comp.(V). 3mm Diam. 63mm Clamp. 220-280dN Hold. 330dN HighStrengthPin Weight. 7,5Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DCA63.1</p>  <p>HeavyDuty SteelBody Diam. 63mm Clamp. 700dN Hold. 770dN HighStrengthPin PinØ. 20-40mm Weight. 7,3Kg.</p> <p>PDF Catalogue</p>
<p>Sublevel UnderbodyClamp DPA50</p>  <p>SteelBody Diam. 50mm Clamp. 400dN Hold. 470dN Weight. 6,2Kg.</p> <p>PDF Catalogue</p>			

RIBALTATORI PNEUMATICI - PIVOT UNITS

<p>Ribaltatore Pneumatico Pivot Unit RFM.2/RF.2</p>  <p>SBI Brake System Hydraulic Control Angles Changeable D. 100-125-160-200 Ang. 15°-129° 190-800Nm (90°)</p> <p>PDF Catalogue</p>	<p>Ribaltatore Pneumatico Pivot Unit RCM.2/RC.2</p>  <p>Angles Changeable Hydraulic Control D. 100-125-160-200 Ang. 15°-129° 190-800Nm (90°)</p> <p>PDF Catalogue</p>	<p>Ribaltatore Pneumatico Pivot Unit RP80.2</p>  <p>Diam. 80 Flat Cylinder Ang. 15-135° 100Nm (90°)</p> <p>PDF Catalogue</p>	<p>Ribaltatore Elettrico Electric Pivot Unit GRE</p>  <p>ServoMotor 400V ServoAxis Controlled Ang. 0-135° Torque: 500Nm Hold: 2.000Nm 3,5 Sec. 0°-->135° Weight: 61Kg.</p> <p>PDF Catalogue</p>
<p>Ribaltatore Elettrico Electric Pivot Unit GRE-FESTO</p>  <p>FESTO ServoMotor 680V ServoAxis Controlled Ang. 0-135° Torque: 500Nm Hold: 2.000Nm 3,2 Sec. 0°-->135° Weight: 47Kg.</p> <p>PDF Catalogue</p>			

UNITA' LINEARI - LINEAR UNITS - (1/2)

<p>Unità Lineare Linear Unit SLD.1</p>  <p>SBI Lock System 2 Work Positions Stroke Changeable D. 40-50-63-80-125 Stroke. 1-500mm Payload. 40-600Kg. Weight. 9,5-305 Kg.</p> <p>PDF Catalogue</p>	<p>Unità Lineare Linear Unit SLDS.2</p>  <p>Clamps Lock System 2 Work Positions Stroke Changeable Diam. 63-80-125 Stroke. 1-500mm Payload. 150-600Kg. Weight. 54-285 Kg.</p> <p>PDF Catalogue</p>	<p>Unità Lineare Linear Unit SLG40</p>  <p>LightWeight Pin Lock System 2 Work Positions Stroke Changeable Diam. 40 Stroke. 1-300 mm Payload. 25 Kg. Weight. 6,5-9,0 Kg.</p> <p>PDF Catalogue</p>	<p>Unità Lineare Linear Unit SLCP63</p>  <p>Togle Lock System 1 Work Positions Stroke Changeable Diam. 63 Stroke. 5-90 mm Payload. 15 Kg. Weight. 8,0 Kg.</p> <p>PDF Catalogue</p>
--	---	--	--

UNITA' LINEARI - LINEAR UNITS Continue (2 of 2) ----->

Leeren Sie den Webbrowser-Cache, so können Sie die aktuellste Version der Kataloge oder 3Ds herunterladen / Cancel your web browser cache in order to be sure to download the last release catalogues or 3Ds



UNITA' LINEARI - LINEAR UNITS - (2/2)

<p>Unità Lineare Elettrica Servo Linear Unit</p> <p>SLDE</p>   <p>Servo Unit SBI Lock System 4 Work Positions Stroke Changeable Sizes. 63-80 Stroke. 0-500mm Payload. 150-250Kg.</p> <p>PDF Catalogue</p>	<p>Unità Lineare Elettrica Servo Linear Unit</p> <p>SE80</p>   <p>ServoMotor 400V ServoAxis Controlled Stroke 0-250mm 3,0 Sec. 0-250mm Stroke 0-500mm 4,5 Sec. 0-500mm Payload. 250Kg.</p> <p>PDF Catalogue</p>	<p>Unità Lineare Elettrica Servo Linear Unit</p> <p>SE 3D XYZ</p>   <p>NEW Customized 3D XYZ ServoMotor AxisControlled</p> <p>Example: Strokes 500mm Payload. 200Kg.</p> <p>Info</p>
---	---	---

MOLTIPLICATORI DI FORZA - FORCE MULTIPLIERS

<p>Moltiplicatore di Forza Force Multipliers</p> <p>FM100</p>   <p>SteelBody Diam. 100mm FwStroke. 50-200mm PwStroke. 8mm FW Force. 460daN PW Force. 4.500daN Weight. 20,5-26,5Kg.</p> <p>PDF Catalogue</p>
--

Leeren Sie den Webbrowser-Cache, so können Sie die aktuellste Version der Kataloge oder 3Ds herunterladen / Cancel your web browser cache in order to be sure to download the last release catalogues or 3Ds